



CONCEPTS NREC



Integrated Turbopump Thermo-Mechanical Design and Analysis Tools

September 12, 2001


Mike Platt



Summary


- Steady and transient thermo-mechanical effects drive life, reliability, and cost
- Design cycle needs upfront consideration of:
 - fits, clearance, preload
 - cooling requirements
 - stress levels, LCF limits, HCF margin
- Data synthesis is needed from component design tools






SBIR Tool Development


- Use LNG turbopump design during feasibility study
 - 630 gpm at 29.6 krpm
 - 37 lbm/s
- Utilize existing component analysis tools to drive assembly models
- Integration into collaborative environment, not just interfacing separate tools




Current Design System




Meanline



3D Blading & CFD




Stress & Vibration




- Captures blade and disk stress, vibration, thermals
- Misses radial and axial preload effects, thermal conduction through bore




Current Design System




Meanline



3D Blading & CFD







Stress & Vibration



- Captures blade and disk stress, vibration, thermals
- Misses radial and axial preload effects, seal interaction, bore conduction




Current Design System



- Captures nominal bearing, seal, and shaft design
- Misses radial and axial preload effects



Thermo-Mechanical Design Tools



- Utilize data from component design tools
 - Rotor, shaft, housing geometry
 - Primary flow from pump and turbine
 - Internal cooling flow
 - Bearing, seal, and shaft design




Thermo-Mechanical Design Tools


- Temperature, stress, deflection
- Blade clearance, seal clearance, bearing race interference
- Thrust load, bearing preload
- Rotor clamp loads, shaft torque
- Stress results feed probabilistic models



ANSYS 5.6.2
JUN 21 2001
08:03:11
NODAL SOLUTION
STEP=1
SUB =1
TIME=1
TEMP (AVG)
RSYS=0
PowerGraphics
EFACET=1
AVRES=Mat
SMN =-252
SMX =65.195




ANSYS 5.6.2
JUN 21 2001
16:30:04
NODAL SOLUTION
STEP=1
SUB =1
TIME=1
USUM (AVG)
RSYS=0
PowerGraphics
EFACET=1
AVRES=Mat
DMX =.122076
SMX =.122076
0
.013564
.027128
.040692
.054256
.06782
.081384
.094948
.108512
.122076




ANSYS 5.6.2
JUN 21 2001
16:27:47
NODAL SOLUTION
STEP=1
SUB =1
TIME=1
SEQV (AVG)
PowerGraphics
EFACET=1
AVRES=Mat

DMX =.122076
SMN =14.536
SMX =177818
0
16000
32000
48000
64000
80000
96000
112000
128000
144000




Life & Confidence Goals


Fixed Confidence Level



Fixed Number of Cycles



Typical Transient Results




Goals for Design Tool Integration

- Collaborative working environment
- Integrate with existing component design and analysis tools
- Direct data sharing, including CAD files
- Extensible to other solvers and applications
- Preserve intellectual property




Integration with CAD Kernel


- Consistent and open data format
- Combine geometry and analytical results
- Direct support for native CAD files




Design Tool Integration



Integration with Parasolid Data



Integration with Design Framework



Conclusions

- Thermo-mechanical analysis tool provides upfront design capability
- Existing component design tools are effectively leveraged
- Dual-use capability will give a broad user base
- Parasolid kernel allows collaboration with a wide applications base

